B50 滑入式迷你铰链(一段力)
Slide-on Mini Hinge (One-way)

描述 Description

开启角度: 95°
铰杯直径: Φ26mm
铰杯深度: 10.3mm
面板(K)尺寸:3-5mm
可选用板厚: 12-18mm

Opening angle: 95°
Diameter of hinge cup: Φ26mm
Depth of hinge cup: 10.3mm
Door (K) dimension:3-5mm
Optional door thickness: 12-18mm

材料 Material

铰杯:铁镀镍
铰臂:铁镀镍
底座:铁镀镍

Hinge cup: Iron with nickel plating
Hinge arm: Iron with nickel plating
Hinge plate: Iron with nickel plating

订购 Order

全盖 Full overlay	半盖 Half overlay	内掩 Inset
订货号 Item no.	订货号 Item no.	订货号 Item no.
有制 With spring: B50-00	有制 With spring: B50-08	有制 With spring: B50-17

铰杯开孔 Drilling For Cup



M38

配件 Accessories

M8胶粒 M8 Dowel	M10胶粒 M10 Dowel	欧式螺丝 Euro Screw
订货号 Item no.	订货号 Item no.	订货号 Item no.
M8	M10	ES

快装胶粒 Expanding Dowel	木牙螺丝 Chipboard Screw	双桥胶粒 Double-bridge Dowel
		
订货号 Item no.	订货号 Item no.	订货号 Item no.
ED	K4X16	S32

型号 Model. B50-HO

注:可配的安装底座与配件,请查询263-270页。

铰链应用系统
26杯轻型门板标准应用

Hinge Application System
Thin Door Standard Application For 26 Cup Hinge

KEA祥兴

全盖 Full overlay	半盖 Half overlay	内掩 Inset

盖位计算表 Overlay Table

H= 底座高度
D= 侧板上所需盖位
K= 门板外线与铰杯钻孔距离
A= 门与侧板间隙

H=Height of hinge base
D=Required overlay on side board
K=Distance between door edge and drilling holes on hinge cup
A=Gap between door and side board

调节范围 Adjustment Range



上下调节	盖位调节	门缝调节
±1.5mm	+5mm	+2.5mm

H=15+K-D	H=6+K-D	H=-6+K+A
		

面板重叠尺寸

D \ H \ K	3	4	5
0	15	16	17
2	13	14	15
4			

面板重叠尺寸

D \ H \ K	3	4	5
0	5	6	7
2	3	4	5
4			

面板重叠尺寸

A \ H \ K	3	4	5
0	1	0	-1
2	3	2	1
4			

开门所需最小间隙 Minimum Gap Required To Door Opening

K=门板钻孔到门板边沿距离
T=门板厚度
A=门板与柜侧的距离
L=门板与侧板的距离

K=Distance between door drilling holes and door edge
T=Door thickness
A=Distance between door panel and side cabinet
L=Gap between door and panel

有倒角边的门的最小距离(半径=1毫米)
Minimum distance for doors with chamfered edges (radius=1 mm)



A \ K \ T	12	13	14	15	16	17	18
3	0.0	0.0	0.1	0.6	1.2	1.7	2.2
4	0.0	0.0	0.0	0.5	1.0	1.5	2.1
5	0.0	0.0	0.0	0.3	0.9	1.4	1.9
6	0.0	0.0	0.0	0.2	0.7	1.2	1.8



L \ K \ T	12	13	14	15	16	17	18
3	1.0	1.0	1.0	1.0	1.0	1.0	1.0
4	1.0	1.0	1.0	1.0	1.0	1.0	1.0
5	1.0	1.0	1.0	1.0	1.0	1.0	1.0
6	1.0	1.1	1.2	1.3	1.4	1.5	1.6