FA19

卡式内置阻尼玻璃铰链(二段力)
Clip-on Glass Soft-closing Hinge (Two-way)

105° | 48 Hours salt-spray test | Soft-closing

描述 Description

开启角度: 105°
铰杯直径: Φ35mm
面板(K)尺寸:3-7mm
可选用板厚: 4-7mm

Opening angle: 105°
Diameter of hinge cup: Φ35mm
Door (K) dimension:3-7mm
Optional door thickness: 4-7mm

材料 Material

铰杯:铁镀镍
铰臂:铁镀镍
底座:铁镀镍
配件:尼龙塑料

Hinge cup: Iron with nickel plating
Hinge arm: Iron with nickel plating
Hinge plate: Iron with nickel plating
Accessories:Nylon plastic

订购 Order

全盖 Full overlay	订货号 Item no.	半盖 Half overlay	订货号 Item no.	内掩 Inset	订货号 Item no.
二段力内置阻尼 Two-way soft-closing	FA19-00	二段力内置阻尼 Two-way soft-closing	FA19-08	二段力内置阻尼 Two-way soft-closing	FA19-17

铰杯开孔 Drilling For Cup



配件 Accessories

欧式螺丝 Euro Screw	订货号 Item no.	双桥胶粒 Double-bridge Dowel	订货号 Item no.	木牙螺丝 Chipboard Screw	订货号 Item no.
10.3, Φ6.3	ES	7.8, 32, Φ5	S32	Φ4, Φ8, 16	K4X16

杯帽 Cup Caps	订货号 Item no.	杯帽 Cup Caps	订货号 Item no.	臂装饰盖 Arm Cap	订货号 Item no.
黑	黑圆 Black KB1	黑	黑拱 Black KB2	KEA	FAC
银	铬圆 Chrome KC1	银	铬拱 Chrome KC2		
黄	金圆 Brass KG1	黄	金拱 Brass KG2		

型号 Model.	型号 Model.	型号 Model.	型号 Model.	型号 Model.	型号 Model.
F15-HO	F15-HOS	F16-HOY			

注:可配的安装底座与配件,请查询263-270页。

铰链应用系统 Hinge Application System
玻璃门标准应用 Glass Door Standard Application

KEA祥兴

全盖 Full overlay

半盖 Half overlay

内掩 Inset

盖位计算表 Overlay Table

H= 底座高度 — H=Height of hinge base
D= 侧板上所需盖位 — D=Required overlay on side board
K= 门板外线与铰杯钻孔距离 — K=Distance between door edge and drilling holes on hinge cup
A= 门与侧板间隙 — A=Gap between door and side board

调节范围 Adjustment Range

上下调节	盖位调节	门缝调节
±1.5mm	+7.5mm	+2.5mm

H=14+K-D



H=5+K-D



H=-5+K+A



面板重叠尺寸

D \ H \ K	3	4	5	6	7
0	18	19	20	21	22
2	16	17	18	19	20
4					

面板重叠尺寸

D \ H \ K	3	4	5	6	7
0	10	11	12	13	14
2	8	9	10	11	12
4					

面板重叠尺寸

A \ H \ K	3	4	5	6	7
0	1	0	-1	-2	-3
2	3	2	1	0	-1
4					